Arcair.



N7500 Gouging System




# ARCAIR-MATIGATION OF THE PROPERTY OF THE PROPE

AUTOMATED GOUGING SYSTEM

www.thermadyne.com/arcair







Ensures conformity to pre-determined, pre-selected groove depth

while maintaining a tolerance of +/-0.025" (0.635 mm) throughout the length of the gouge.





### Digital LCD Remote Pendant

- Ease of use start/stop function, travel delay, electrode diameter
- Rough machining feature to stall the feed of the electrode to compensate for pitted area or out-of-round steel rolls, thereby maintaining the concentricity of the shaft/roll
- "Travel delay" function assures excellent groove geometry at the very beginning of the groove, thereby eliminating the need for a starting pad
- Shock-absorbent bumper
- \* Patent Pending

Torch Head

\* Redesigned Torch Head with an extended front end – gives the operator better view of the weld seam that's being back-gouged

\* Can be oriented 360 degrees in any direction giving flexibility to fit the application



## Digital Circuitry Control Box

- \* Redesigned digital circuitry control box
- A synergic mode ensures conformity to pre-determined, pre-selected groove depth and width specifications

Arcair®, the industry leader in air carbon-arc products, introduces the Arcair-Matic® N7500, a next generation automatic gouging system that provides superior performance, flexibility, versatility, and safety.

Covering a broad range of applications, the Arcair-Matic N7500 gouging system can be utilized on almost all metals, including stainless steel, carbon, manganese, and chrome-moly steels. It is perfect for applications on pressure vessels, wind towers, shipbuilding, railroads, bridge and girder manufacturing, and with heavy equipment used in mining industries.

As a bonus feature, use the remote pendant to track actual arc time to help schedule routine maintenance; additionally, it enables you to monitor and manage cost of the gouging project / job.

The heavy duty remote pendant is enclosed in a splash-proof panel to operate in high humidity/outside conditions and is designed to withstand high impact.

The Arcair-Matic N7500 can be used with CC/CV power supplies available in the industry. It utilizes the contactor in the welding power supply unit thereby eliminating the need for the external contactor used in prior models.

The multi input voltage platform enables use in all markets around the world, servicing both US (110VAC) and International (220VAC).

The N7500 is equipped with important safety features that will shut down the system if it senses no current or low voltage. These functions ensure optimum groove quality and prevent damage to the equipment and work.

All functions can be controlled. from determining gouge parameters, start/stop function, travel delay, and the capability to manually feed or retract the electrode in the torch head. The operator can view the amperage and voltage during gouging sequence easily while maintaining




# VERSATILITY

A single electrode contact shoe assembly accepts the entire range of Arcair Jetrods® Jointed electrodes from 5/16" (7.9 mm) through 3/4" (19.1 mm).



# IMPROVED PRODUCTIVITY

Faster metal removal over any other conventional means in today's market. A gouge depth of 1.5 times the diameter can be achieved in a single pass while providing a machine-like U or V-shaped groove.



# ORDERING INFORMATION



### Complete N7500 Gouging System

Includes Remote Pendant, Control Box and Torch Head (Part No. 65-991-015)

# System Cable Assembly Options\*

110V AC Power	Supply Cable
Part No.	Description
96-130-304	10 ft (3 m)
220V AC Power	Supply Cable
Part No.	Description
96-130-305	10 ft (3 m)
Pendant Cable	Assembly
Part No.	Description
THE RESERVE THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLU	

14" (0.36 m)

15 ft (5 m)

25 ft (8 m)

50 ft (15 m)

96-170-069

96-170-070

96-170-071

96-170-072


_	96-130-
-	96-130-
	Power
	Cable
	Part No
	96-130-
	96-130-
	96-130-

Motor Cable	e Assembly
Part No.	Description
96-130-335	3 ft (0.9 m)
96-130-336	15 ft (5 m)
96-130-337	25 ft (8 m)
96-130-338	50 ft (15 m)
<b>Power Suppl</b>	ly Communication
Cable Assem	bly
Part No.	Description
96-130-339	15 ft (5 m)
96-130-340	25 ft (8 m)
96-130-341	50 ft (15 m)

DC Power Cables		
Part No.	Description	
96-130-254	4 ft (1.2 m)	
96-130-256	15 ft (5 m)	
96-130-300	25 ft (8 m)	
NOTE: Minimum 2	Power Cables Required	
Air Hose As	sembly	
Part No.	Description	
94-396-051	4 ft (1.2 m)	
94-396-049	15 ft (5 m)	
94-396-048	25 ft (8 m)	
1 000 010	20 11 (0 11)	

\*Must be ordered separately

# N7500 Assembly Set-Up







A Global Cutting & Welding Market Leader"

U.S. Customer Care: 800-426-1888 / FAX 800-535-0557 \* Canada Customer Care: 905-827-4515 / FAX 800-588-1714 International Customer Care: 940-381-1212 / FAX 940-483-8178

www.thermadyne.com/arcair