

VULCANO

1800W 120A



TIPO / TYPE



EQUIPAMIENTO / FEATURES



DOTACIÓN / INCLUDED



EMBALAJE / PACKAGING



RECAMBIOS FRECUENTES / FREQUENT SPARE PARTS



Ref. 400001



Ref. 400065



Ref. 400014



Ref. 400040



Ref. 400046



Ref. 400055

MODELO / MODEL

GENERADOR GENERATOR	Voltaje - Frecuencia / Voltage - Frequency AC 230V Máxima / Maximum AC 230V Nominal / Rated
SOLDADOR WELDING	DC Máxima / Maximum DC Nominal / Rated Ciclo de trabajo 180A - 160A / Duty cycle 180A - 160A
Modelo motor / Engine model	
Cilindrada / Displacement	
Tipo de motor / Engine type	
Nivel sonoro a 7mts / Sound level to 7m	
Nivel de potencia acústica garantizada LwA acorde 2000/14/EC enmienda 2005/88/EC Guaranteed sound power level LwA pursuant to 2000/14/EC amended by 2005/88/EC	
Tipo de arranque / Startup type	
Capacidad depósito combustible / Fuel tank capacity	
Consumo hora - Autonomía al 25% 50% 75% carga / Hourly consumption - Autonomy at 25% 50% 75% loads	
Capacidad de aceite - Tipo aceite / Oil capacity - Type of oil	
Kit de transporte / Transportation kit	
Dimensiones L x A x Alto (cm) / Dimensions L x W x H (cm)	
Peso máquina / bruto embalaje (Kg) / Machine weight / gross packaging (Kg)	
Referencia / Reference	

VULCANO

230V - 50Hz
1800W
1500W
120A
100A
50% - 70%
SG70
210cc
Gasolina, 4 tiempos OHV refrigeración forzada por aire Gasoline, 4-stroke OHV, air forced cooling
71dB (A)
96dB (A)
Manual / Recoil
3.6L
(0.8 l/h - 4.5h) (1 l/h - 3,6h) (1.2 l/h - 3h)
0.6L SAE10W30 - SAE10W40
Si, con neumáticos goma 8" y llanta metálica Yes, with 8" rubber tires and metal rim
60 x 51 x 45
46 / 50
2013042